

WELLHEAD BALL VALVES



ABCO Subsea is bringing to market a line of new Subsea Wellhead Ball Valves with a proprietary ROV-friendly handle that can be operated with the valve in any orientation. The Valves are 4" reduced port with Stainless Steel trim.

Advantages:

- Robust wrap-around handle cannot be accidentally removed
- Proprietary deep-stabbing feature on pin nose
- Threaded ends coated with molybdenum disulfide
- Can be equipped with ROV Pipe End Caps for redundant sealing
- Can be equipped with hammer union if required



7108 West Little York Road
Houston, Texas 77040

713.871.8020

sales@ABCOSubsea.com

ABCOSubsea.com

WELLHEAD BALL VALVES Technical Data



Material Specs:

Nominal Size	4 inches
Weight in Air	109 lbs (49.4 kg)
Weight in Water	95 lbs (43.1 kg)
Size envelope	29.5" (750 mm) x 12.5" (318 mm) x 7.5" (191 mm)
Pressure rating	2,500 psi
Valve operation	¼ turn by ROV
Wellhead interface	4 inch line pipe
Pressure cap interface	O-Ring and modified stub acme



7108 West Little York Road

Houston, Texas 77040

713.871.8020

sales@ABCOSubsea.com

ABCOSubsea.com